



Film Specifications

RESIDENTIAL AND COMMERCIAL FILMS
on 1/8 inch clear glass



UV Clear and Blackout films block 98% or more of UV rays. White Frost rejects 88% or more of UV rays.

FILM TYPE	COLOR	VISIBLE LIGHT TRANSMISSION	SOLAR ENERGY REJECTION	VISIBLE LIGHT REFLECTANCE (Exterior)	SHADING COEFFICIENT	SOLAR HEAT GAIN COEFFICIENT	U-FACTOR NFRC	SOLAR ABSORPTION	GLARE REDUCTION
CLEAR GLASS	clear	89%	14%	8%	0.99	0.86	1.04	10%	0%

Specialty Series

DECORATIVE SPECIAL APPLICATION FILMS

UV Clear	clear	90%	16%	8%	0.97	0.84	1.10	12%	0%
White Frost	white	74%	24%	15%	0.84	0.73	1.10	17%	17%
Blackout	black	0%	70%	6%	0.36	0.30	1.10	94%	100%

All of Johnson Window Films are protected by CST™ scratch resistant hardcoat.

Specifications represent film mounted to 1/8 inch (3mm) clear glass.

Tests, equipment and methods are in accordance with ASTM, ANSI and NFRC standards. Values expressed hereof are typical and provided for comparative purposes only.



Johnson® Window Films

Manufactured by Johnson Laminating & Coating, Inc.
Carson, California USA

www.johnsonwindowfilms.com